


## Goof Off Professional Strength VOC Aerosol

HEALTH	*	2
FLAMMABILITY		4
PHYSICAL		0
PPE		X



Printed: 09/13/2012  
Revision: 09/13/2012  
Supersedes Revision: 06/02/2011

## 1. Product and Company Identification

**Product Code:** A2420  
**Product Name:** Goof Off Professional Strength VOC Aerosol  
**Manufacturer Information**  
**Company Name:** W. M. Barr  
2105 Channel Avenue  
Memphis, TN 38113  
**Phone Number:** (901)775-0100  
**Emergency Contact:** 3E 24 Hour Emergency Contact (800)451-8346  
**Information:** W.M. Barr Customer Service (800)398-3892  
**Web site address:** www.wmbarr.com  
**Preparer Name:** W.M. Barr EHS Dept (901)775-0100  
**Intended Use:** Multi-Purpose Remover for tar, ink, paint, adhesive, etc.  
**Synonyms**  
FG658, FG658B

## 2. Hazards Identification

**GHS Hazard Phrases**

No data available.

**GHS Precaution Phrases**

No data available.

**GHS Response Phrases**

No data available.

**GHS Storage and Disposal Phrases**

No data available.

**Potential Health Effects (Acute and Chronic)****INHALATION:**

ACUTE (IMMEDIATE): Causes respiratory tract irritation.

CHRONIC (DELAYED): May be harmful if inhaled.

**SKIN:**

ACUTE (IMMEDIATE): Causes skin irritation.

CHRONIC (DELAYED): May cause defatting of skin after prolonged or repeated exposure. This product can be absorbed through skin.

**EYE:**

ACUTE (IMMEDIATE): Causes severe eye irritation.

CHRONIC (DELAYED): No Data Available

**INGESTION:**

ACUTE (IMMEDIATE): May cause irritation to the mouth, throat, and stomach. Aspiration hazard if swallowed - may enter lungs and cause damage.

CHRONIC (DELAYED): May be harmful if ingested.

# SAFETY DATA SHEET

## Goof Off Professional Strength VOC Aerosol

Page: 2  
Printed: 09/13/2012  
Revision: 09/13/2012  
Supersedes Revision: 06/02/2011

MUTAGENIC EFFECTS: No data available

CARCINOGENIC EFFECTS: This product contains ethylbenzene, which has been determined by NTP to be an animal carcinogen with no known relevance to humans. IARC has classified ethylbenzene as possibly carcinogenic to humans (2b) on the basis of sufficient evidence of carcinogenicity in laboratory animals but inadequate evidence of cancer in humans.

REPRODUCTIVE EFFECTS: No data available

OTHER ACUTE EFFECTS: No data available

OTHER CHRONIC EFFECTS: This product contains ingredients that may contribute to the following potential chronic health effects: Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

### Recommended Exposure Limits

#### Europe

" Acetone (67-64-1): TWAs: (500 ppm TWA; 1210 mg/m<sup>3</sup> TWA)

" Benzene, ethyl- (100-41-4): TWAs: (100 ppm TWA; 442 mg/m<sup>3</sup> TWA) | STELs: (200 ppm STEL; 884 mg/m<sup>3</sup> STEL) | Skin Absorbers: (possibility of significant uptake through the skin)

" Xylene (1330-20-7): TWAs: (50 ppm TWA; 221 mg/m<sup>3</sup> TWA) | STELs: (100 ppm STEL; 442 mg/m<sup>3</sup> STEL) | Skin Absorbers: (possibility of significant uptake through the skin)

#### US STATE CALIFORNIA

" Acetone (67-64-1): PELs: (750 ppm PEL; 1780 mg/m<sup>3</sup> PEL) | STELs: (1000 ppm STEL; 2400 mg/m<sup>3</sup> STEL) | Ceilings: (3000 ppm Ceiling)

" Benzene, ethyl- (100-41-4): PELs: (100 ppm PEL; 435 mg/m<sup>3</sup> PEL) | STELs: (125 ppm STEL; 545 mg/m<sup>3</sup> STEL)

" Xylene (1330-20-7): PELs: (100 ppm PEL; 435 mg/m<sup>3</sup> PEL) | STELs: (150 ppm STEL; 655 mg/m<sup>3</sup> STEL) | Ceilings: (300 ppm Ceiling)

" Propane (74-98-6): PELs: (1000 ppm PEL; 1800 mg/m<sup>3</sup> PEL)

#### United States - OSHA

" Acetone (67-64-1): TWAs: (1000 ppm TWA; 2400 mg/m<sup>3</sup> TWA) | TWAs: (750 ppm TWA; 1800 mg/m<sup>3</sup> TWA) | STELs (Short Term Exposure Limits): (1000 ppm STEL; 2400 mg/m<sup>3</sup> STEL (The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors))

" Benzene, ethyl- (100-41-4): TWAs: (100 ppm TWA; 435 mg/m<sup>3</sup> TWA) | TWAs: (100 ppm TWA; 435 mg/m<sup>3</sup> TWA) | STELs (Short Term Exposure Limits): (125 ppm STEL; 545 mg/m<sup>3</sup> STEL)

" Xylene (1330-20-7): TWAs: (100 ppm TWA; 435 mg/m<sup>3</sup> TWA) | TWAs: (100 ppm TWA; 435 mg/m<sup>3</sup> TWA) | STELs (Short Term Exposure Limits): (150 ppm STEL; 655 mg/m<sup>3</sup> STEL)

" Propane (74-98-6): TWAs: (1000 ppm TWA; 1800 mg/m<sup>3</sup> TWA) | TWAs: (1000 ppm TWA; 1800 mg/m<sup>3</sup> TWA)

#### United States - ACGIH

" Acetone (67-64-1): TWAs: (500 ppm TWA) | STELs: (750 ppm STEL) | Carcinogens: (A4 - Not Classifiable as a Human Carcinogen) | TLV Basis - Critical Effects: (irritation) | BEIs: (Acetone in urine: 50 mg/L, end of shift (Ns))

" Benzene, ethyl- (100-41-4): TWAs: (100 ppm TWA) | STELs: (125 ppm STEL) | Carcinogens: (A3 - Confirmed animal carcinogen with unknown relevance to humans) | TLV Basis - Critical Effects: (irritation);

## Goof Off Professional Strength VOC Aerosol

Printed: 09/13/2012

Revision: 09/13/2012

Supercedes Revision: 06/02/2011

CNS) | BEIs: (Mandelic acid in urine: 1.5 g/g creatinine, end of shift at end of workweek (Ns); Ethyl benzene in end-exhaled air: (Sq)) | Notice of Intended Changes (BEIs): (Sum of mandelic acid and phenyl glyoxylic acid in urine: 1.5 g/g creatinine, end of shift at end of workweek (Ns, Sq); Ethyl benzene in end-exhaled air: not critical (Sq))

" Xylene (1330-20-7): TWAs: (100 ppm TWA) | STELs: (150 ppm STEL) | Carcinogens: (A4 - Not Classifiable as a Human Carcinogen) | TLV Basis - Critical Effects: (irritation) | BEIs: (Methylhippuric acids in urine: 1.5 g/g creatinine, end of shift)

" Propane (74-98-6): TWAs: (1000 ppm TWA (listed under aliphatic hydrocarbon gases alkane C1-C4)) | TLV Basis - Critical Effects: (CNS depression; cardiac sensitization)

## United States - NIOSH

" Acetone (67-64-1): TWAs: (250 ppm TWA; 590 mg/m<sup>3</sup> TWA)

" Benzene, ethyl- (100-41-4): STELs: (125 ppm STEL; 545 mg/m<sup>3</sup> STEL) | TWAs: (100 ppm TWA; 435 mg/m<sup>3</sup> TWA)

" Propane (74-98-6): TWAs: (1000 ppm TWA; 1800 mg/m<sup>3</sup> TWA)

## Germany

" Acetone (67-64-1): MAKs: (500 ppm MAK; 1200 mg/m<sup>3</sup> MAK) | Ceilings: (1000 ppm Peak; 2400 mg/m<sup>3</sup> Peak) | TWAs: (500 ppm TWA; 1200 mg/m<sup>3</sup> TWA) | BAT - Werte: (80 mg/L; Parameter = Acetone; Material = urine; Sampling time = end of exposure/shift)

" Benzene, ethyl- (100-41-4): Skin Absorbers: (Skin Absorber) | Carcinogens: (Category 3A (could be carcinogenic for man)) | Skin Absorbers: (Skin absorber) | TWAs: (100 ppm TWA; 440 mg/m<sup>3</sup> TWA) | BAT - Werte: (1 mg/L; Parameter = Ethylbenzol; Material = whole blood; Sampling time = end of exposure/shift; 800 mg/g creatinine; Parameter = Mandelic acid plus Phenylglyoxylic acid; Material = urine; Sampling time = end of exposure/shift)

" Xylene (1330-20-7): MAKs: (100 ppm MAK; 440 mg/m<sup>3</sup> MAK) | Ceilings: (200 ppm Peak; 880 mg/m<sup>3</sup> Peak) | Skin Absorbers: (Skin Absorber) | Pregnancy: (classification not yet possible (all isomers)) | Skin Absorbers: (Skin absorber) | TWAs: (100 ppm TWA; 440 mg/m<sup>3</sup> TWA) | BAT - Werte: (1.5 mg/L; Parameter = Xylol; Material = whole blood; Sampling time = end of exposure/shift; 2 g/L; Parameter = Methylhippuric-(Tolur-)acid; Material = urine; Sampling time = end of exposure/shift)

" Ethanol, 2-(2-butoxyethoxy)- (112-34-5): MAKs: (100 mg/m<sup>3</sup> MAK) | Ceilings: (100 mg/m<sup>3</sup> Peak) | Pregnancy: (no risk to embryo/fetus if exposure limits adhered to) | TWAs: (100 mg/m<sup>3</sup> TWA)

" Propane (74-98-6): MAKs: (1000 ppm MAK; 1800 mg/m<sup>3</sup> MAK) | Ceilings: (2000 ppm Peak; 3600 mg/m<sup>3</sup> Peak) | TWAs: (1000 ppm TWA; 1800 mg/m<sup>3</sup> TWA)

## New Zealand

" Acetone (67-64-1): TWAs: (500 ppm TWA; 1185 mg/m<sup>3</sup> TWA) | STELs: (1000 ppm STEL; 2375 mg/m<sup>3</sup> STEL)

" Benzene, ethyl- (100-41-4): TWAs: (100 ppm TWA; 434 mg/m<sup>3</sup> TWA) | STELs: (125 ppm STEL; 543 mg/m<sup>3</sup> STEL)

" Xylene (1330-20-7): TWAs: (50 ppm TWA; 217 mg/m<sup>3</sup> TWA) |

" Propane (74-98-6): Simple Asphyxiants: (simple asphyxiant)

**Signs and Symptoms Of Exposure**

ROUTE OF ENTRY: Inhalation, Skin/Dermal, Eye/Ocular, Ingestion/Oral

TARGET ORGANS: Central Nervous System (CNS), Blood and/or Immune System, Liver, Kidney

**Medical Conditions Generally Aggravated By Exposure**

Skin and Respiratory Conditions

# SAFETY DATA SHEET

## Goof Off Professional Strength VOC Aerosol

Page: 4  
Printed: 09/13/2012  
Revision: 09/13/2012  
Supersedes Revision: 06/02/2011

### OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

### 3. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Concentration
1. Acetone {2-Propanone}	67-64-1	60.0 -100.0 %
2. Hydrotreated light distillate (petroleum)	64742-47-8	7.0 -13.0 %
3. Xylene (mixed isomers) {Benzene, dimethyl-}	1330-20-7	5.0 -10.0 %
4. Ethylbenzene {Ethylbenzol; Phenylethane}	100-41-4	1.0 -5.0 %
5. Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	112-34-5	3.0 -7.0 %
6. Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	68476-86-8	7.0 -13.0 %

### 4. First Aid Measures

#### Emergency and First Aid Procedures

**INHALATION:** Move injured person into fresh air and keep person calm under observation. Get medical attention immediately.

**SKIN:** Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

**EYE:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. If medical assistance is not immediately available, flush an additional 15 minutes. Get medical attention immediately.

**INGESTION:** Rinse mouth with water. Give one or two glasses of water. Only induce vomiting at the instruction of medical personnel. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head lower than hips to prevent aspiration. Get medical attention immediately.

### 5. Fire Fighting Measures

**Flash Pt:** < 0 F (-17.8 C) Method Used: Setaflash Closed Cup (Rapid Setaflash)

**Explosive Limits:** LEL: 1 % UEL: 13 %

**Autoignition Pt:** No data available.

#### Fire Fighting Instructions

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

#### Flammable Properties and Hazards

Flashpoint of liquid concentrate: 0 degrees F.

Flashpoint of propellant: -138.23 degrees F.

LEL of propellant: 1.8 %

Level 3 Aerosol

#### Hazardous Combustion Products

Carbon monoxide and carbon dioxide.

#### Suitable Extinguishing Media

Carbon dioxide, dry chemical, foam and/or water fog.

#### Unsuitable Extinguishing Media

None known.

## 6. Accidental Release Measures

### Steps To Be Taken In Case Material Is Released Or Spilled

**PERSONAL PRECAUTIONS:** Use self-containing breathing apparatus or air-mask for large spills in a confined area. Avoid contact with eyes.

**EMERGENCY PROCEDURES:** Ventilate the area. Avoid breathing dust or vapor. Remove all sources of ignition. Use only non-sparking tools.

**ENVIRONMENTAL PRECAUTIONS:** Do not allow spilled material to enter waterways.

**CONTAINMENT/CLEAN-UP MEASURES:** Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures.

## 7. Handling and Storage

### Precautions To Be Taken in Handling

Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

### Precautions To Be Taken in Storing

Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 Section 22.

Empty containers may contain product residue, including flammable or explosive vapors.

Level 3 Aerosol

### Other Precautions

Keep away from heat, sparks and open flame. No smoking.

## 8. Exposure Controls/Personal Protection

Hazardous Components (Chemical Name)	CAS #	OSHA PEL	ACGIH TWA	Other Limits
1. Acetone {2-Propanone}	67-64-1	PEL: 1000 ppm	TLV: 500 ppm STEL: 750 ppm	No data.
2. Hydrotreated light distillate (petroleum)	64742-47-8	No data.	TLV: 200 mg/m3	No data.
3. Xylene (mixed isomers) {Benzene, dimethyl-}	1330-20-7	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm	No data.
4. Ethylbenzene {Ethylbenzol; Phenylethane}	100-41-4	PEL: 100 ppm	TLV: 100 ppm STEL: 125 ppm	No data.
5. Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	112-34-5	No data.	No data.	No data.
6. Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	68476-86-8	No data.	No data.	No data.

### Respiratory Equipment (Specify Type)

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

# SAFETY DATA SHEET

## Goof Off Professional Strength VOC Aerosol

Page: 6  
Printed: 09/13/2012  
Revision: 09/13/2012  
Supersedes Revision: 06/02/2011

### Eye Protection

Chemical goggles, also wear a face shield if splashing hazard exists.

### Protective Gloves

Appropriate chemical resistant gloves should be worn that are compatible with the ingredients, such as rubber or nitrile.

### Other Protective Clothing

To prevent skin contact wear protective clothing covering all exposed areas.

Various application methods can dictate the use of additional protective safety equipment, such as impermeable aprons to minimize exposure.

### Engineering Controls (Ventilation etc.)

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas.

Where the product is used in a hazardous classified area, use explosion-proof electrical/ventilating/lighting/equipment. Use only with adequate ventilation to prevent buildup of vapors.

Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.

### Work/Hygienic/Maintenance Practices

A source of clean water should be available in the work area for flushing of eyes and skin.

Wash hands thoroughly after use and before eating, drinking, or smoking.

## 9. Physical and Chemical Properties

<b>Physical States:</b>	[ X ] Gas	[ X ] Liquid	[ ] Solid
<b>Melting Point:</b>	No data.		
<b>Boiling Point:</b>	No data.		
<b>Autoignition Pt:</b>	No data.		
<b>Flash Pt:</b>	< 0 F (-17.8 C) Method Used: Setaflash Closed Cup (Rapid Setaflash)		
<b>Explosive Limits:</b>	LEL: 1 %	UEL: 13 %	
<b>Specific Gravity (Water = 1):</b>	No data.		
<b>Density:</b>	6.725 (of - concentrate) LB/GL		
<b>Vapor Pressure (vs. Air or mm Hg):</b>	No data.		
<b>Vapor Density (vs. Air = 1):</b>	> 1		
<b>Evaporation Rate:</b>	> 1		
<b>Solubility in Water:</b>	Partial		
<b>Percent Volatile:</b>	99 % by weight.		
<b>VOC / Volume:</b>	20 % WT		

### Appearance and Odor

Colorless, transparent, solvent odor.

## 10. Stability and Reactivity

**Stability:** Unstable [ ] Stable [ X ]

### Conditions To Avoid - Instability

Heat

### Incompatibility - Materials To Avoid

Strong oxidizing and reducing agents.

### Hazardous Decomposition Or Byproducts

Carbon monoxide and carbon dioxide.

**Possibility of Hazardous Reactions:** Will occur [ ] Will not occur [ X ]

### Conditions To Avoid - Hazardous Reactions

No data available.

## 11. Toxicological Information

### Toxicological Information

This product has not been tested as a whole. Information below will be for individual ingredients.

Acetone: Inhalation LC50 Mouse: 44 g/m<sup>3</sup>/4H; Oral LD50 Rat: 5800 mg/kg

Benzene, ethyl- : Oral LD50 Rat: 3500 mg/kg; Dermal LD50 Rabbit: 17800 µL/kg

Xylene : Inhalation LC50 Rat: 5000 ppm/4H; Oral LD50 Rat: 4300 mg/kg; Dermal LD50 Rabbit: >1700 mg/kg

Ethanol, 2-(2-butoxyethoxy)- : Oral LD50 Rat: 5660 mg/kg; Dermal LD50 Rabbit: 2700 mg/kg

### Chronic Toxicological Effects

This product has not been tested as a whole. Information below will be for individual ingredients.

Germ Cell Mutagenicity: No information available for the product.

Reproductive Toxicity: No information available for the product.

STOT-Single Exposure: No information available for the product.

STOT-Repeated Exposure: No information available for the product.

### Carcinogenicity/Other Information

IARC 2B - Possibly Carcinogenic to Humans

IARC 3: Not Classifiable as to Carcinogenicity in Humans.

ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

ACGIH A4 - Not Classifiable as a Human Carcinogen.

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1. Acetone {2-Propanone}	67-64-1	n.a.	n.a.	A4	n.a.
2. Hydrotreated light distillate (petroleum)	64742-47-8	n.a.	n.a.	A4	n.a.
3. Xylene (mixed isomers) {Benzene, dimethyl-}	1330-20-7	n.a.	3	A4	n.a.
4. Ethylbenzene {Ethylbenzol; Phenylethane}	100-41-4	n.a.	2B	A3	n.a.

## Goof Off Professional Strength VOC Aerosol

Printed: 09/13/2012

Revision: 09/13/2012

Supercedes Revision: 06/02/2011

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
5. Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	112-34-5	n.a.	n.a.	n.a.	n.a.
6. Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	68476-86-8	n.a.	n.a.	n.a.	n.a.

## 12. Ecological Information

**General Ecological Information**

ECOLOGICAL FATE: No information available for the product.

PERSISTANCE/DEGRADABILITY: No information available for the product.

BIOACCUMULATION POTENTIAL: No information available for the product.

MOBILITY IN SOIL: No information available for the product.

## 13. Disposal Considerations

**Waste Disposal Method**

Dispose of waste at an approved hazardous waste treatment/disposal facility in accordance with applicable local, provincial and federal regulations.

## 14. Transport Information

**LAND TRANSPORT (US DOT)**

DOT Proper Shipping Name Consumer Commodity ORM-D

**LAND TRANSPORT (Canadian TDG)**

TDG Shipping Name Consumer Commodity ORM-D

**Additional Transport Information**

The shipper / supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

For D.O.T. information, contact W.M. Barr Technical Services at 1-800-398-3892.

## 15. Regulatory Information

**Canadian Chemical Lists**

Hazardous Components (Chemical Name)	CAS #	Canadian NPRI	Canadian IDL
1. Acetone {2-Propanone}	67-64-1	No	Yes
2. Hydrotreated light distillate (petroleum)	64742-47-8	Yes	No
3. Xylene (mixed isomers) {Benzene, dimethyl-}	1330-20-7	Yes	No
4. Ethylbenzene {Ethylbenzol; Phenylethane}	100-41-4	Yes	Yes
5. Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	112-34-5	Yes	Yes
6. Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	68476-86-8	No	No

**Canadian WHMIS Classification**

No data available.

**US EPA SARA Title III**

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. Acetone {2-Propanone}	67-64-1	No	Yes 5000 LB	No	Yes



## Goof Off Professional Strength VOC Aerosol

Printed: 09/13/2012

Revision: 09/13/2012

Supercedes Revision: 06/02/2011

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
2. Hydrotreated light distillate (petroleum)	64742-47-8	No	No	No	No
3. Xylene (mixed isomers) {Benzene, dimethyl-}	1330-20-7	No	Yes 100 LB	Yes	Yes
4. Ethylbenzene {Ethylbenzol; Phenylethane}	100-41-4	No	Yes 1000 LB	Yes	Yes
5. Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	112-34-5	No	No	Yes-Cat. N230	No
6. Liquefied petroleum gas, sweetened {propane, isobutane, n-butane}	68476-86-8	No	No	No	No

**US EPA CAA, CWA, TSCA**

Hazardous Components (Chemical Name)	CAS #	EPA CAA	EPA CWA NPDES	EPA TSCA	CA PROP 65
1. Acetone {2-Propanone}	67-64-1	HAP, ODC ()	No	Inventory, 4 Test	No
2. Hydrotreated light distillate (petroleum)	64742-47-8	HAP, ODC ()	No	Inventory	No
3. Xylene (mixed isomers) {Benzene, dimethyl-}	1330-20-7	HAP, ODC ()	Yes	Inventory	No
4. Ethylbenzene {Ethylbenzol; Phenylethane}	100-41-4	HAP, ODC ()	Yes	Inventory, 4 Test	Yes
5. Diethylene glycol monobutyl ether {2-(2-Butoxyethoxy)ethanol {(a glycol ether)}	112-34-5	HAP, ODC ()	No	Inventory, 4 Test	No
6. Liquefied petroleum gas, sweetened {propane, isobutane, n-butane}	68476-86-8	HAP, ODC ()	No	Inventory	No

**International Regulatory Lists****EPA Hazard Categories:**

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

Yes  No Acute (immediate) Health Hazard

Yes  No Chronic (delayed) Health Hazard

Yes  No Fire Hazard

Yes  No Sudden Release of Pressure Hazard

Yes  No Reactive Hazard

**Regulatory Information**

This product has been classified according to the hazard criteria of the Controlled Products Regulations.

Concentrations reported in section 2 are weight/weight.

Ingredients disclosed in section 2 are on Canadian DSL.

**Regulatory Information Statement**

All components of this material are listed on the TSCA Inventory or are exempt.

**16. Other Information****Company Policy or Disclaimer**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.