

## Uline

Teflon Tape Rolls

Manufacturer MSDS Number: 0195.015

### SECTION 1 : Chemical Product and Company Identification

**MSDS Name:** Teflon Tape Rolls

**Distributor Name:** Uline

**Distributor Address:**

2200 S. Lakeside Drive  
Waukegan, IL 60085

Phone: (800) 295-5510

**Product Description:**

General: PTFE/fiberglass tapes, with pressure sensitive silicone or acrylic adhesive on one side.

**Manufacturer MSDS Revision Date:**

January 10, 1995

Supersedes: March 27, 1986

**Manufacturer Product Codes:**

--	--	--	--

### SECTION 2 : Hazardous Ingredients/Identity Information

**Hazardous Paragraph:**

The above product(s) are considered "articles" according to OSHA Hazard Communication Standard 29 CFR 1910.1200 and, as such, are exempt from the material safety data sheet provisions of 29 CFR 1910.1200 (G) (8).

These products are considered non-hazardous when used according to accepted practices for the intended use.

### SECTION 3 : Physical And Chemical Characteristics

**Physical State/Appearance:**

Flexible, adhesive-backed tape, various thicknesses.

**Color:**

Various colors.

**Solubility:**

In Water: Insoluble

FlashPoint:  
Not Applicable

#### SECTION 4 : Fire And Explosion Hazards

Flash Point:  
Not Applicable

Extinguishing Media:  
Foam, carbon dioxide, dry chemical.

Fire Fighting Instructions:  
Wear face mask and self-contained breathing apparatus approved by U.S. Bureau of Mines if there is a danger of inhaling smoke from a fire involving and fluorocarbon.

Unusual Fire Hazards:  
Product is difficult to ignite and will ordinarily not burn once the source of ignition is removed. In an extreme fire situation, protection from hydrogen fluoride should be employed.

#### SECTION 5 : Health Hazards

##### Applies to All Ingredients:

Route of Exposure:  
Not Applicable

Potential Health Effects:  
Acute: Exposure to fumes generated if the product is heated above 230 deg C may result in "Polymer Fume Fever".

Chronic Health Effects:  
Exposure to fumes generated if the product is heated above 230 deg C may result in "Polymer Fume Fever".

Signs/Symptoms:  
"Polymer Fume Fever" -- flu-like symptoms (chills, fever, tightness in the chest), appearing two or more hours after exposure and subsiding within 36 to 48 hours, even in the absence of treatment.

#### SECTION 6 : Emergency And First Aid Procedures

Inhalation:  
Remove patient to fresh air; call physician.

#### SECTION 7 : Reactivity Data

Chemical Stability:

Stable.

**Hazardous Decomposition Products:**

Toxic gaseous material (HF and fluorocarbon olefins) may be evolved above 230 deg C.

**SECTION 8 : Precautions For Safe Handling**

**Spill Cleanup Measures:**

Not Applicable

**Handling:**

Provide proper local and general ventilation if product is heated above 230 deg C. Avoid contamination of smoking materials; do not smoke while cutting, heat sealing, or fabricating material.

**Waste Disposal:**

Landfill is preferred; burring not recommended. With incineration, gaseous products should be removed by alkaline scrubbing.

**SECTION 9 : Control Measures**

**SECTION 10 : Other Information**

**Applies to all ingredients:**

**OSHA 29 CFR 1200:**

The above product(s) are considered "articles" according to OSHA Hazard Communication Standard 29 CFR 1910.1200 and, as such, are exempt from the material safety data sheet provisions of 29 CFR 1910.1200 (G) (8).

**MSDS Revision Date:**

January 10, 1995  
Supersedes: March 27, 1986